

jQuery API

[New or Changed in 1.6](#)
[Raw XMLAPI Dump](#)
[Dynamic API Browser](#)
[jQuery API Book](#)

Keyboard navigation now available! Use up, down, tab, shift+tab, shift+upArrow and enter to navigate.

Browse the jQuery API

[All](#)[- Ajax](#)[Global Ajax Event Handlers](#)[Helper Functions](#)[Low-Level Interface](#)[Shorthand Methods](#)[Attributes](#)[Core](#)[CSS](#)[Data](#)[Deferred Object](#)[Dimensions](#)[+ Effects](#)[+ Events](#)[Forms](#)[Internals](#)[+ Manipulation](#)[+ Miscellaneous](#)[Offset](#)[+ Plugins](#)[+ Properties](#)[+ Selectors](#)[+ Traversing](#)[Utilities](#)[+ Version](#)

Ajax

The jQuery library has a full suite of AJAX capabilities. The functions and methods therein allow us to load data from the server without a browser page refresh.

jQuery.ajax()

Perform an asynchronous HTTP (Ajax) request.

[Low-Level Interface](#)

.ajaxComplete()

Register a handler to be called when Ajax requests complete. This is an [Ajax Event](#).

[Global Ajax Event Handlers](#)

.ajaxError()

Register a handler to be called when Ajax requests complete with an error. This is an [Ajax Event](#).

[Global Ajax Event Handlers](#)

jQuery.ajaxPrefilter()

Handle custom Ajax options or modify existing options before each request is sent and before they are processed by `$.ajax()`.

[Low-Level Interface](#)

.ajaxSend()

Attach a function to be executed before an Ajax request is sent. This is an [Ajax Event](#).

[Global Ajax Event Handlers](#)

jQuery.ajaxSetup()

Set default values for future Ajax requests.

[Low-Level Interface](#)

.ajaxStart()

Register a handler to be called when the first Ajax request begins. This is an [Ajax Event](#).

[Global Ajax Event Handlers](#)

.ajaxStop()

Register a handler to be called when all Ajax requests have completed. This is an [Ajax Event](#).

[Global Ajax Event Handlers](#)

.ajaxSuccess()

Attach a function to be executed whenever an Ajax request completes successfully. This is an [Ajax Event](#).

[Global Ajax Event Handlers](#)

jQuery.get()

Load data from the server using a HTTP GET request.

[Shorthand Methods](#)

jQuerygetJSON()

Load JSON-encoded data from the server using a GET HTTP request.

[Shorthand Methods](#)

jQuery.getScript()

Load a JavaScript file from the server using a GET HTTP request, then execute it.

[Shorthand Methods](#)

.load()

Load data from the server and place the returned HTML into the matched element.

[Shorthand Methods](#)

jQuery.param()

Create a serialized representation of an array or object, suitable for use in a URL query string or Ajax request.

[Collection Manipulation](#), [Forms](#), [Helper Functions](#)

jQuery.post()

Load data from the server using a HTTP POST request.

[Shorthand Methods](#)

.serialize()

Encode a set of form elements as a string for submission.


[Forms](#), [Helper Functions](#)

.serializeArray()

Encode a set of form elements as an array of names and values.

[Forms](#), [Helper Functions](#)

© 2010 [The jQuery Project](#)

Sponsored by  [Media Temple](#) and
 others.

[Download](#)

[Documentation](#)

[Tutorials](#)

[Bug Tracker](#)

[Discussion](#)